

3100psi
3500psi
4000psi

GENERAC®

Commercial Power Washers

3100/3500/4000psi

1 of 2

Model	UPC	Emissions Certification
3100psi @ 2.8 gpm		
5993-2	6 96471 05993 9	49-State
5994-0	6 96471 05994 6	50-State
3500psi @ 3.6 gpm		
6416-0	6 96471 06416 2	49-State
4000psi @ 4.0 gpm		
5997-2	6 96471 05997 7	49-State



features

POWERFUL GENERAC OHV ENGINE

- Features low oil shutdown to protect the engine.

PROFESSIONAL-GRADE TRIPLEX PUMP

- Ceramic-coated pistons mean long life.

PROFESSIONAL-GRADE SPRAY GUN

- Adjustable side handle provides precise control.
- Cushion grip and easy-to-pull trigger reduce fatigue and improve comfort.

PRESSURE CONTROL VALVE

- Provides complete control of water pressure for all applications.

QUICK-CLICK™ NOZZLE TIPS

- Five included, for tackling any job.

USER FRIENDLY CONTROLS

- All in a single location, including on/off, choke, and fuel shutoff.

NON-MARRING, STEEL-REINFORCED HOSE

- Will not leave scuff marks on surfaces.
- Quick connectors make hose connections a snap.

DURABLE WELDED ROLL-CAGE STYLE FRAME

- Protects the engine and pump.
- Front and back grab bars make it easier to lift.

Commercial Power Washers

specifications by model

Outlet Pressure - (PSI)/(BAR)	3100/213	3500/241	4000/276
Flow Rate - (GPM)/(Liters/min)	2.8/10.6	3.6/13.6	4.0/15.1
Retail (49 State)	59932	64160	59972
Engine			
Engine Manufacturer	Generac	Generac	Generac
Engine Displacement (Cubic Inch)/(cc)	12.9/212	18.4/302	25.6/420
Engine Type	OHV (Over Head Valve)	OHV (Over Head Valve)	OHV (Over Head Valve)
Engine Orientation	Horizontal	Horizontal	Horizontal
Low Oil Shut Down System	Yes	Yes	Yes
Fuel Capacity - (Quarts)/(Liters)	3.6/3.5	5.8/5.5	6.8/6.5
Fuel On/Off Switch	Yes	Yes	Yes
Oil Capacity - (Oz)/(Liters)	20/0.6	37/1.1	37/1.1
Recommended Engine Oil	SAE 30 or 10W30	SAE 30 or 10W30	SAE 30 or 10W30
Throttle Control	Manual	Manual	Manual
Choke	Manual	Manual	Manual
Starting Method	Manual	Manual	Manual
On/Off Switch	Yes	Yes	Yes
Pump			
Pump Type	Triplex	Triplex	Triplex
Plunger	Ceramic Coated Stainless Steel	Ceramic Coated Stainless Steel	Ceramic Coated Stainless Steel
Material	Aluminum Body & Brass Head	Aluminum Body & Brass Head	Aluminum Body & Brass Head
Misc	Double seal system with oversized bearings	Double seal system with oversized bearings	Double seal system with oversized bearings
Water supply temperature (°F)/(°C)	100/38 Max		
Hose			
Hose length - (Feet)/(Meters)	35/10.7	35/10.7	50/15.2
Hose Material	Non-Marring, Steel Reinforced Polyurethane (Gray)		
Hose Dia. (Inch) / (mm)	3/8 / 9.5	3/8 / 9.5	3/8 / 9.5
Hose Rating	4000psi	4000psi	4000psi
Hose Connectors	Quick Change	Quick Change	Quick Change
Detergent System			
Chemical Tank(s) Number per unit	0	0	0
Chemical Tank(s) - Description	Siphon Hose	Siphon Hose	Siphon Hose

Nozzles			
Nozzles - Number per unit	5	5	5
Nozzles - Description	0, 15, 25,40, Soap	0, 15, 25,40, Soap	0, 15, 25,40, Soap
Gun & Lance			
Gun	Professional w/ adjustable side handle	Professional w/ adjustable side handle	Professional w/ adjustable side handle
Gun to Lance Connection	M22 Threaded	M22 Threaded	M22 Threaded
Gun to Hose Connection	Quick Change	Quick Change	Quick Change
Lance Length (Inch/CM)	20/51	33/84	33/84
Lance to Nozzle Connection	Quick Change	Quick Change	Quick Change
Lance Material	Stainless Steel	Stainless Steel	Stainless Steel
Lance Connector Material	Brass	Brass	Brass
Warranty			
Warranty	3 Yr. Limited	3 Yr. Limited	3 Yr. Limited
Frame & Misc.			
Handle	Folding	Folding	Folding
Construction	Welded Steel (Roll Cage Design)	Welded Steel (Roll Cage Design)	Welded Steel (Roll Cage Design)
Wheels	3" x 10" Never Flat	3" x 10" Never Flat	4" x 12" Pneumatic
Dimensions and Weights			
Unit Dimensions (Inches) (Handle in folded position)			
Length (L)	24 1/2	27 3/4	27 3/4
Height (H)	28 3/4	31 7/8	31 7/8
Unit Dimensions (Inches) and Weight (lbs) (Handle extended)			
Length (EL)	31 3/4	34 1/2	34 1/2
Width (W) [Wheel to Wheel]	24 1/2	26 3/4	28 1/4
Height (EH)	38	42 1/2	42 1/2
Unit weight including hose, gun & lance (lbs)	102.5	129	146.5
Actual boxed weight	120	150	164
Actual boxed length	26	29	29
Actual boxed width	25.5	28	28
Actual boxed height	31	33.5	33.5