

3000psi  
3500psi  
4000psi

# GENERAC®

## Industrial Power Washers

3000/3500/4000psi

1 of 2

Model	UPC
<b>3000psi @ 3.0 gpm</b>	
6228-0	6 96471 06228 1
<b>3500psi @ 3.7 gpm</b>	
6229-0	6 96471 06229 8
<b>4000psi @ 3.4 gpm</b>	
6230-0	6 96471 06230 4

Emissions Certification: 50-State



## features

### POWERFUL SUBARU ENGINE

- Features low oil shutdown to protect the engine.

### PROFESSIONAL-GRADE TRIPLEX PUMP

- Ceramic pistons mean long life.

### PROFESSIONAL-GRADE SPRAY GUN

- Adjustable side handle provides precise control.
- Cushion grip and easy-to-pull trigger reduce fatigue and improve comfort.

### PRESSURE CONTROL VALVE

- Provides complete control of water pressure for all applications.

### QUICK-CLICK™ NOZZLE TIPS

- Four included, for tackling any job.

### USER FRIENDLY CONTROLS

- All in a single location, including on/off, choke, and fuel shutoff.

### NON-MARRING, STEEL-REINFORCED RUBBER HOSE

- Will not leave scuff marks on surfaces.
- Quick connectors make hose connections a snap.

### DURABLE HEAVY DUTY STYLE FRAME

- Protects the engine and pump.
- Front grab bar makes it easier to lift.

# Industrial Power Washers

## specifications by model

Outlet Pressure - (PSI)/(BAR)	3000/207	3500/241	4000/276
Flow Rate - (GPM)/(Liters/min)	3.0/11.4	3.7/14.0	3.4/12.9
Retail (50 State)	06228	06229	06230
<b>Engine</b>			
Engine Manufacturer	Subaru	Subaru	Subaru
Engine Displacement (Cubic Inch)/(cc)	16.2/265	24.7/404	24.7/404
Engine Type	OHC (Over Head Cam)	OHC (Over Head Cam)	OHC (Over Head Cam)
Engine Orientation	Horizontal	Horizontal	Horizontal
Low Oil Shut Down System	Yes	Yes	Yes
Fuel Capacity - (Quarts)/(Liters)	6.4/6.1	7.4/7.0	7.4/7.0
Fuel On/Off Switch	Yes	Yes	Yes
Oil Capacity - (Oz)/(Liters)	33.8/1.0	40.6/1.2	40.6/1.2
Recommended Engine Oil	SAE 30 or 10W30	SAE 30 or 10W30	SAE 30 or 10W30
Throttle Control	Manual	Manual	Manual
Choke	Manual	Manual	Manual
Starting Method	Manual	Manual	Manual
On/Off Switch	Yes	Yes	Yes
<b>Pump</b>			
Pump Type	Triplex		
Plunger	Ceramic		
Material	Aluminum Body & Brass Head		
Misc	Double seal system with oversized bearings, Thermal relief, Water inlet filter with clear sleeve for screen inspection		
Water supply temperature (°F)/(°C)	100/38 Max		
<b>Hose</b>			
Hose length - (Feet)/(Meters)	50/15.2		
Hose Material	Non-Marring, Steel Reinforced Rubber (Gray)		
Hose Dia. (Inch) / (mm)	3/8 / 9.5		
Hose Rating	4000psi		
Hose Connectors	Quick Change		

<b>Nozzles</b>			
Nozzles - Number per unit	4		
Nozzles - Description	0, 15, 25,40		
<b>Gun &amp; Lance</b>			
Gun	Professional w/ adjustable side handle	Professional w/ adjustable side handle	Professional w/ adjustable side handle
Gun to Lance Connection	M22 Threaded	M22 Threaded	M22 Threaded
Gun to Hose Connection	Quick Change	Quick Change	Quick Change
Lance Length (Inch/CM)	20/51	33/84	33/84
Lance to Nozzle Connection	Quick Change	Quick Change	Quick Change
Lance Material	Stainless Steel	Stainless Steel	Stainless Steel
Lance Connector Material	Brass	Brass	Brass
<b>Warranty</b>			
Warranty	Limited	Limited	Limited
<b>Frame &amp; Misc.</b>			
Handle	Installed	Installed	Installed
Construction	Durable Heavy Duty Design	Durable Heavy Duty Design	Durable Heavy Duty Design
Wheels	5" x 13" Pneumatic	5" x 13" Pneumatic	5" x 13" Pneumatic
<b>Dimensions and Weights</b>			
<b>Unit Dimensions (Inches) and Weight (lbs)</b>			
Length (L)	39.5	39.5	39.5
Width (W) [Wheel to Wheel]	28.5	28.5	28.5
Height (H)	26.0	26.0	26.0
Dry weight including hose, gun & lance (lbs)	178	191	191
Shipping Weight	232	245	245