

2500 psi
2700 psi
3100 psi

GENERAC[®]

Residential Power Washers

2500/2700/3100

1 of 2

Model	UPC:	Emissions Certification
2500psi @ 2.3 gpm		
6020-2	6 96471 06020 1	49-State
2700psi @ 2.3 gpm		
6022-2	6 96471 06022 5	49-State
6023-0	6 96471 06023 2	50-State
3100psi @ 2.7 gpm		
6024-2	6 96471 06024 9	49-State
6025-0	6 96471 06025 6	50-State



features

GENERAC OHV ENGINE

- Low Oil Shutdown on all Models

EASY ACCESS

- Axial cam pump is well above the ground, making hose connections easy.
- Engine Controls (clearly marked for easy starting)

MOBILITY

- Balanced for almost effortless mobility, regardless of terrain.
- Pump height makes it easy to gather hoses for transport.

COMFORT

- Cushion Grip (provides greater comfort while cleaning)
- Easy-to-pull trigger reduces fatigue.
- Longer gun – improved grip surface.
- Rear hose connection on spray gun provides better balance and comfort.

COMPACT DESIGN

- Doesn't take up much room in the garage or shed

Residential Power Washers

specifications by model

Outlet Pressure - (PSI)/(BAR)	2500/172	2700/186	3100/213
Flow Rate - (GPM)/(Liters/min)	2.3/7.6	2.3/7.6	2.7/10.2
(49 State)	60202	60222	60242
CARB certified (50 State)	N/A	60230	60250
Engine			
Engine Manufacturer	Generac	Generac	Generac
Engine Displacement (Cubic Inch)/(cc)	11.9/196	11.9/196	12.9/212
Engine Type	OHV (Over Head Valve)	OHV (Over Head Valve)	OHV (Over Head Valve)
Engine Orientation	Horizontal	Horizontal	Horizontal
Net Torque	12.4N.m (9.1 lb.ft)/2500rpm	12.4N.m (9.1 lb.ft)/2500rpm	12.5N.m (9.2 lb.ft)/3000rpm
Gross Power	6.5 Hp / 3600rpm	6.5 Hp / 3600rpm	7.0 Hp / 4000rpm
Low Oil Shut Down System	Yes	Yes	Yes
Fuel Capacity - (Quarts)/(Liters)	3.6/3.5	3.6/3.5	3.6/3.5
Fuel On/Off Switch	Yes	Yes	Yes
Oil Capacity - (Oz)/(Liters)	20/0.6	20/0.6	20/0.6
Recommended Engine Oil	SAE 30 or 10W30	SAE 30 or 10W30	SAE 30 or 10W30
Throttle Control	Manual	Manual	Manual
Choke	Manual	Manual	Manual
Starting Method	Manual	Manual	Manual
On/Off Switch	Yes	Yes	Yes
Pump			
Pump Type	Axial Cam	Axial Cam	Axial Cam
Plunger	Stainless Steel	Stainless Steel	Stainless Steel
Material	Aluminum Body & Head	Aluminum Body & Head	Aluminum Body, Brass Head
Misc	Oversized Bearings	Oversized Bearings	Double seal system with oversized bearings
Water supply temperature (°F)/(°C)	100/38 Max		
Hose			
Hose length - (Feet)/(Meters)	25/7.6	25/7.6	30/9.1
Hose Dia. (Inch) / (mm)	1/4 / 6.4	1/4 / 6.4	1/4 / 6.4
Hose Rating	3100psi	3100psi	3100psi
Hose Connectors	M22 Threaded	M22 Threaded	M22 Threaded

Detergent System			
Chemical Tank(s) Number per unit	0	1	2
Chemical Tank(s) - Description	Siphon Hose	3/4 Gallon	3/4 Gallon
Nozzles			
Nozzles - Number per unit	3	4	5
Nozzles - Description	0, 25, Soap	0, 25, 40, Soap	0, 15, 25, 40, Soap
Gun & Lance			
Gun	Standard	Standard	Deluxe
Gun to Lance Connection	M22 Threaded	M22 Threaded	M22 Threaded
Gun to Hose Connection	M22 Threaded	M22 Threaded	M22 Threaded
Lance Length (Inch/CM)	20/51	20/51	20/51
Lance to Nozzle Connection	Quick Change	Quick Change	Quick Change
Lance Material	Chrome Plated Steel	Chrome Plated Steel	Chrome Plated Steel
Lance Connector Material	Brass	Brass	Brass
Warranty			
Warranty	2 Yr. Limited	2 Yr. Limited	2 Yr. Limited
Frame & Misc.			
Handle	Fixed	Fixed	Fixed
Construction	Welded Steel	Welded Steel	Welded Steel
Wheels	1.5" x 10" Never Flat	1.5" x 10" Never Flat	1.5" x 10" Never Flat
Dimensions and Weights			
Unit Dimensions (Inches) and Weight (lbs)			
Length (L)	23 1/4	23 1/4	23 1/4
Width (W) [Wheel to Wheel]	16	16	16
Height (H)	40 1/2	40 1/2	40 1/2
Unit weight including hose, gun & lance (lbs)	60.3	61.5	67.5
Actual boxed weight	68	69	74
Actual boxed length	27.0	27.0	27.0
Actual boxed width	17.5	17.5	17.5
Actual boxed height	21.0	21.0	21.0